

# LTU Long-Range





### Mechanical

Dimensions	512.5 x 385.75 x 258.3 mm (20.18 x 15.19 x 10.17")	
Weight	Without mount: 1.36 kg (2.9 lb) With mount: 1.74 kg (3.8 lb)	
Enclosure material	Outdoor UV-stabilized polycarbonate	
Mount materials	Polycarbonate, metal	
Mounting	Pole-mount (Kit included)	
Wind loading	550 N at 200 km/h (123.6 lbf at 125 mph)	
Wind survivability	200 km/h (125 mph)	

#### Hardware

Networking interface	(1) GbE RJ45 port		
Power method	24V passive PoE (Pairs 4, 5+; 7, 8-)		
Power supply	24V, 0.5A Gigabit PoE adapter (Included)		
Supported voltage range	22-26V		
Max. power consumption	8.5W		
ESD/EMP protection	Air/contact: ± 24kV		
Button	Factory reset		
Operating temperature	-40 to 60° C (-40 to 140° F)		
Operating humidity	5 to 95% noncondensing		
Certifications	FCC, IC, CE		

#### Software

Modes	PtMP CPE, PtP *1.5.1 and later 1.5.x series firmware.		
Services	SNMP, SSH, dynamic DNS, webserver, remote log, ping watchdog		
Utilities	airView®, speed test, alignment, discovery, ping, traceroute, cable test, constellation		
Auto distance adjustment	Yes		
Power adjustment	Yes		
Network	Bridge/Router* mode *Router mode is available in PtMP CPE mode only.		
Security	Yes		
Management interface	Bluetooth management for easy setup over UISP App WEB UI		
Minimum software requirements	Any modern web browser iOS™ or Android™ based smartphone		

## System

Maximum throughput 900+ Mbps\*

\*FWversion 230 and later.



Encryption	WPA2-PSK (AES)
Uplink/Downlink ratio	25/75, 33/67, 50/50

## RF

Operating frequency*		U-NII-1	5150 - 5250 MHz			
	LIC/CA	U-NII-2A	5250 - 5350 MHz			
	US/CA	U-NII-2C	5470 - 5725 MHz			
		U-NII-3	5725 - 5850 MHz			
	Worldwide	4800 - 6200 MHz				
	*Depends on regulatory region.					
Management radio	2400 - 2483.5 MHz	2400 - 2483.5 MHz				
Max. conducted TX power	22 dBm (Per chain)	22 dBm (Per chain)				
Channel bandwidth	10/20/30/40/50/60/80/100 N *FW version 2.30 and later.	10/20/30/40/50/60/80/100 MHz* *FWversion 230 and later.				
Antenna gain	26 dBi	26 dBi				

