



Switching WiFi Camera Security Door Access CloudKeys & Gateways Power Tech New II

CloudKeys & Gateways > Gateway Lite

Datasheet In The Box Marketing Images Installation Guide





Mechanical

Dimensions 98 x 98 x 30 mm (3.9 x 3.9 x 1.2")

Weight 320 g (11.3 oz)

Enclosure material Polycarbonate

Hardware

Processor Dual-core ARM® Cortex®-A53 at 1 GHz

Memory information 1 GB DDR3L

Management interface Ethernet

Bluetooth 5.1

Networking interface LAN:

(1) GbE RJ45 port

WAN:

(1) GbE RJ45 port

Power method USB type C (5V/3A)

Supported voltage range 100-240V

Max. power consumption 3.83W

Ambient operating temperature -10 to 40° C (14 to 104° F)

Ambient operating humidity 5 to 95% noncondensing

Certifications CE, FCC, IC

Gateway Features

Performance WiFi QoS with UniFi APs

Application, domain, and country-based QoS Application and device type identification Internet quality and outage reporting

Next-generation security Application-aware firewall rules

Signature-based IPS/IDS threat detection Content, country, domain, and ad filtering VLAN/subnet-based traffic segmentation

Full stateful firewall

Advanced networking License-free SD-WAN*

WireGuard, L2TP and OpenVPN server

OpenVPN client

OpenVPN and IPsec site-to-site VPN

One-click Teleport* and Identity Enterprise VPN**

Policy-based WAN and VPN routing

DHCP relay

Customizable DHCP server

IPv6 ISP support

*When paired with a CloudKey or Official UniFi Hosting.

**When paired with a CloudKey.

Application Requirements

UniFi Network

Version 8.0.7 and later

